



CORRECTIONAL FACILITY DISPOSERS



"A" Series



"B" Series



"C" Series

DISPOSER:

- Includes all standard features of the disposer series specified with all fasteners tamperproof.



SINK RING OR CONE:

- Has a stainless steel, perforated restrictor plate permanently welded into throat opening. Included with the sink or cone mounting assemblies are: solenoid valve, flow control valve, vacuum breaker and vinyl silver trap scrapping ring.

CORRECTIONAL FACILITY DISPOSERS			
Model No.	PH	HP	Throat Size
A112S-07CP	1½	1	7"
A112P-07CP	1½	3	7"
A2S-07CP	2	1	7"
A2P-07CP	2	3	7"
A3P-07CP	3	3	7"
A5P07CP	5	3	7"
B3P-0CP	3	3	7"
B5P-0CP	5	3	7"
C10P-0CP	10	3	7"

CORRECTIONAL FACILITY SINK RING OR CONE		
Sink Assembly No.	Cone Assembly No. & Size	
A-RSA7CP	A-C712CP	12" Dia.
	A-C715CP	15" Dia.
	A-C718CP	18" Dia.
B-RSACP	B-C12CP	12" Dia.
	B-C15CP	15" Dia.
	B-C18CP	18" Dia.
C-RSACP	C-C12CP	12" Dia.
	C-C15CP	15" Dia.
	C-C18CP	18" Dia.



RAC2 Series (Shown)

CORRECTION FACILITY CONTROLS						
Model No. RAC1 Series	Model No. RAC2 Series	HP Range	Voltages			PH
			L	H	Hertz	
RAC1-KP	RAC2-KP	½, ¾, 1¼, 1½, 2, 3, 5	200-240/440-480		50/60	3
RAC1-BE	RAC2-BE	½, ¾, 1¼, 1½, 2, 3, 5	380-415		50	3
RAC1-SL	RAC2-SL	½, ¾, 1¼, 1½, 2	110-120		50/60	1
RAC1-SH	RAC2-SH	½, ¾, 1¼, 1½, 2	200-240		50/60	1
RAC1-7*	RAC2-7*	7	200-240	440-480	60	3
RAC1-10*	RAC2-10*	10	200-240	440-480	60	3

*Indicate voltage by adding L or H to end of model number

CONTROL:

- Includes all standard features of the control model specified with provision for lockout.

OPTIONAL:

- **CP:** Correctional Package
- **RS:** Remote Start/Stop switch.

INCLUDES:

- **PF:** Positive flush.
- **EM:** The *Eco-Mizer*™ Electricity and Water Saver.

In line with its policy to continually improve its products, Red Goat reserves the right to change materials and specifications without notice.