

SERIES C – 15" TURNTABLE



10 HP
208-230/460 Volts 60HZ. 3 PH

VOLUME TO BE HANDLED – 3,000 POUNDS PER HOUR

SERIES B – 10^{5/8}" TURNTABLE



3 & 5 HP
208-230/460 Volts 50/60 HZ. 3 PH
(Overload Protection in Motor on all Series "B" Disposers)

VOLUME TO BE HANDLED – 2,000 POUNDS PER HOUR

SERIES A – 8" TURNTABLE



1^{1/2}, 2, 3 HP 208-230/460 Volts 50/60 HZ. 3 PH
and 5 HP 208-230/460 Volts 60 HZ. 3 PH
1^{1/2} & 2 HP also available in
115/230 Volts 50/60 HZ. 1 PH
(Overload Protection in Motor on all Series "A" Disposers)

VOLUME TO BE HANDLED – 1,480 POUNDS PER HOUR

SERIES F – 6^{3/8}" TURNTABLE



1/2, 3/4 and 1^{1/4} HP
208-230/460 Volts 50/60 HZ. 3 PH
or
115/230 Volts 50/60 HZ. 1 PH
(Overload Protection in Motor on all Series "F" Disposers)

VOLUME TO BE HANDLED – 240 POUNDS PER HOUR



SOMAT COMPANY
165 Independence Court,
Lancaster, PA 17601
717-397-5100
800-237-6628 ext. 181
FAX 717-397-1997
www.redgoat.com



CONFORMS TO
UL STD 430
CERTIFIED TO CAN/CSA
STD C22.2 NO. 68

ITW Food Equipment Group

Mounting Assembly Options for Red Goat Disposers

Sink Assembly (Series A, B & C)

- (1) Neoprene Silver Saver
- (1) Stainless Steel Sink Adapter
- (1) 1/2" Solenoid Valve (specify voltage)
- (1) 1/2" Vacuum Breaker

Flow Control Valves*

- *Series A - (1) 8 GPM
- *Series B - (1) 3 GPM
- (1) 10 GPM
- *Series C - (2) 10 GPM

Sink Assembly (Series F)

- (1) Sink Stopper
- (1) Mounting Head
- (1) 1/2" Solenoid Valve (specify voltage)
- (1) 1/2" Vacuum Breaker
- (1) 3 GPM Flow Control Valve

Part #	Description
H-RSA	"F" Series Sink Mounting Assembly
H-C12	"F" Series Cone Assembly (12" opening)
H-C18	"F" Series Cone Assembly (18" opening)
A-RSA4 or 7	"A" Series Sink Mounting Assembly 4 1/2" or 7"
A-C712	"A" Series Cone Assembly (12" opening)
A-C718	"A" Series Cone Assembly (18" opening)
B-RSA	"B" Series Sink Mounting Assembly
B-C12	"B" Series Cone Assembly (12" opening)
B-C18	"B" Series Cone Assembly (18" opening)

Cone Assembly (Series A, B, C, F)

- Cone - 12", 15", or 18"
- Water Swirl
- Silver Saver
- 1/2" Solenoid Valve (specify voltage)
- Flow Control Valves*
- *Series A - (1) 8 GPM
- *Series B - (1) 3 GPM
- (1) 10 GPM
- *Series C - (2) 10 GPM

For Red Goat "C" Series Mounting Assemblies Contact the Factory.

Model No. RAC1 Series	Model No. RAC2 Series	HP Range	Voltages			PH
			L	H	HERTZ	
RAC1-KP	RAC2-KP	1/2, 3/4, 1 1/4, 1 1/2, 2, 3, 5	200-240/440-480		50/60	3
RAC1-BE	RAC2-BE	1/2, 3/4, 1 1/4, 1 1/2, 2, 3, 5	380-415		50	3
RAC1-SL	RAC2-SL	1/2, 3/4, 1 1/4, 1 1/2, 2	110-120		50/60	1
RAC1-SH	RAC2-SH	1/2, 3/4, 1 1/4, 1 1/2, 2	200-240		50/60	1
RAC1-7*	RAC2-7*	7	200-240	440-480	60	3
RAC1-10*	RAC2-10*	10	200-240	440-480	60	3

* - Indicate Voltage by adding L or H to end of model #.

RAC1
Auto Reverse
Low Voltage/Overload Protection
Timed Water After Run
Timed Motor After Run
Auto Off Feature

RAC2
Auto Reverse
Low Voltage/Overload Protection
Timed Water After Run
Timed Motor After Run
Auto Off Feature
Lighted Push Buttons
Line Disconnect Handle

MC Series
Manual On/Off Switch
Low Voltage/Overload Protection



RMS Series
Drum Switch
Manual-Reversing



MS Series
Manual On/Off Switch



Control Group Options

Part #	Description
RAC1	1/2 to 5 HP for "A", "B", "C" and "F" Disposers
RAC2	1/2 to 5 HP for "A", "B", "C" and "F" Disposers
MC	1/2 to 5 HP Range
MS	1/2 to 5 HP Range
RMS	1/2 to 1 1/4 HP/1 PH - 1/2 to 2 HP/3 PH
RMS	3 to 5 HP/3 PH
RS	Remote Start-Stop (to be used with RAC1 or RAC2 controls—optional)



SOMAT COMPANY
165 Independence Court, Lancaster, PA 17601
717-397-5100 • 800-237-6628 ext. 181
FAX 717-397-1997
www.redgoat.com